

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Exterminator II 35W Monopoint Luminaire

System Type	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
MO	1035	F 55°	827 2700K - 85	2476	3409	BK Black
			830 3000K - 85	2691	3700	BN Brushed Nickel
			835 3500K - 85	2815	3873	WT White
			840 4000K - 85	2828	3886	
			927 2700K - 90	2029	2824	
			930 3000K - 90	2185	3035	
		N 25°	827 2700K - 85	2487	8723	
			830 3000K - 85	2652	9279	
			835 3500K - 85	2773	9710	
			840 4000K - 85	2795	9748	
			927 2700K - 90	2020	7069	
			930 3000K - 90	2176	7517	

Example: **MO-1035F-827-BK**

### DESCRIPTION

The LEDme Exterminator II offers superior light output in a compact, unobtrusive design. The Exterminator II collection was developed for upscale residential and commercial environments. Available in four high powered LED outputs, the 14W version outperforms a 20W HID, the 22W compares to a 35W HID, the 35W compares to a 50W HID, and the 52W compares to a 70W HID. For use with 120V track. Track Fixture is available in H, J/J2, and L track configurations. Order according to track layout specifications.

### FEATURES

- Accommodates 1 lens accessory and 1 glare control accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS


<b>Construction:</b>	Die-cast aluminum with removable front cap for easy change of lenses or accessories
<b>Power:</b>	35W
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5%, 0-10V: 100-5%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Lens:</b>	Clear Tempered Glass
<b>Rated Life:</b>	60000 Hours
<b>Mounting:</b>	Can be mounted on ceiling or wall in all orientations
<b>Finish:</b>	Electroplated Brushed Nickel, Electrostatically Powder Coated Black, Electrostatically Powder Coated White
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, Title 24:

### REPLACEMENT PARTS


- SL-REF-BL18-N - REFLECTORS
- SL-REF-BL18-F - REFLECTORS



### FINISHES



### LINE DRAWING



Fixture Type: \_\_\_\_\_








Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Exterminator II 35W Monopoint Luminaire

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	<b>LENS-20-AMB</b> <b>LENS-20-BLU</b> <b>LENS-20-GRN</b> <b>LENS-20-RED</b>	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i>
	<b>LENS-20-FR</b>	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	<b>LENS-20-SPR</b>	<i>Spread Lens</i>	<i>SpreadLens</i>
	<b>LENS-20-UVF</b>	<i>UV Filter lens</i>	<i>Clear</i>
	<b>LENS-20-BEL</b>	<i>Beam Elongating Lens</i>	<i>BeamElongating</i>
	<b>LENS-20P-CRL-BK</b> <b>LENS-20P-CRL-BN</b> <b>LENS-20P-CRL-PT</b> <b>LENS-20P-CRL-WT</b>	<i>Cross Louver</i> <i>Cross Louver</i> <i>Cross Louver</i> <i>Cross Louver</i>	<i>Black</i> <i>BrushedNickel</i> <i>Platinum</i> <i>White</i>
	<b>LENS-20-SNOOT-BK</b> <b>LENS-20-SNOOT-BN</b> <b>LENS-20-SNOOT-PT</b> <b>LENS-20-SNOOT-WT</b>	<i>Snoot</i> <i>Snoot</i> <i>Snoot</i> <i>Snoot</i>	<i>Black</i> <i>BrushedNickel</i> <i>Platinum</i> <i>White</i>